

**Hallowell<sup>®</sup>**  
**Safety-View™ KD**  
**Wardrobe Lockers**

**General:** Lockers shall Be "**Hallowell Safety-View KD Wardrobe Lockers**" as manufactured by Hallowell, Div. List Industries Inc. or approved equal. Fabricate lockers square, rigid and without warp, with metal faces flat and free from dents or distortion. Make all exposed metal edges safe to touch. Weld frame members together to form rigid, one-piece structure. Weld, bolt, or rivet other joints and connections as standard with manufacturer. Grind exposed welds flush. Do not expose bolts or rivet heads on fronts of locker doors or frames except for fastening of number plates and recessed handle.

**Finishing:** All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade enamel electrostatically sprayed and baked at 325 degrees Fahrenheit for a minimum of 30 minutes to provide a tough durable finish. Color to be selected from manufacturer's standard list of colors. Interior components to be painted #729 Parchment. **Two-Tone Color Combination:** Shall be at no additional cost with the locker frame and trim chosen from one color and the doors may be one of any other color chosen from manufacturers standard selection.

**Frame:** Fabricate of 16 gauge (minimum) channels, with integral continuous door stop/strike formed on both latch and hinge side vertical members. Cross frame members of 16 gauge channel shapes, including intermediate cross frame members on double and triple tier (frames with doors 20" high and higher) lockers shall be securely welded to the vertical framing members to ensure rigidity. Rubber bumpers shall be provided to cushion door closing.

**Safety-View Wardrobe Doors:** Doors 20" high and over to be fabricated from single sheet prime 16 gauge (18 gauge for doors 9" wide) with single bends at top and bottom and double bends at the sides. The channel formed by the double bend at the latch side is designed to fully conceal the lock bar. Doors shall include two clear see-thru polycarbonate panels securely riveted to the inside of the door face located above and below the recessed handle. The see-thru door panels shall consist of a clear, polished surface, ultraviolet-stabilized polycarbonate not less than 3/16" thick to meet building code requirements for a CC-1 rating and be listed with the Underwriters Laboratories for the UL flammability standard and the UL972 standard for burglary resistant glazing materials. Polycarbonate must be approved for Consumer Product Safety Commission (CPSC 16CFR 1201) Categories I & II and ANSI Z97.1-1984 Safety Glazing Standards. Doors shall be Plain (non-louvered).

**Stainless Steel Recessed Locker Handle:** All wardrobe doors shall have recessed stainless steel handle shaped to receive a padlock or built-in combination lock. The recess pan shall be deep enough to have the lock be flush with the outer door face.

## Hallowell<sup>®</sup> Safety-View<sup>™</sup> KD Wardrobe Lockers (Page 2)

**Latch Assembly:** The latching mechanism for wardrobe doors shall be finger lift control type constructed of 14 gauge (minimum) steel with a nylon cover that has a generous finger pull. Spring activated nylon slide latches shall be completely enclosed in the lock channel allowing doors to close with the lock in the locked position. Locking device shall be designed for use with either built-in combination locks or padlocks. Latch hooks shall be securely welded to the vertical frame channel on the strike side to engage the nylon slide latches. Three latch hooks for doors 48" and higher, two latch hooks for doors under 48" high.

**Door Hinges:** Wardrobe doors 20" high and higher shall not be less than 2" long 16 gauge five knuckle pin type, securely welded to frame and riveted to the door. Provide 3 hinges for doors 48" and higher and 2 for doors 20" thru 36" high. All doors to be right hand, side hinged.

**Body:** Fabricate back and sides of 24 gauge (minimum) sheet steel, with double flanged connections extending full height. Form top, bottom and intermediate tier dividers of 24 gauge (minimum) sheet steel with single return bends at all sides. Bolt top and bottom as well as horizontal tier dividers of wardrobe openings to front horizontal frame members at not less than two places in addition to side panels. Form hat shelves at 60" and 72" high single tier lockers of 24 gauge (minimum) sheet steel with single bends at sides and back and a double bend at front.

**Locks (If Required):** Shall be master keyed to one system for the entire project. (See lock use chart for suggested lock application).

**Equipment:** Furnish each locker with the following items, unless otherwise shown.

**Single tier lockers:** Openings 60" and 72" shall include one hat shelf, one double prong ceiling hook and a minimum of two single prong wall hooks.

**Double tier lockers:** Openings 30" and 36" high shall include one double prong ceiling hook and a minimum of two single prong wall hooks.

**Triple tier lockers:** Openings 20" and 24" high shall include one double prong ceiling hook only.

**Two-Year Warranty:** Hallowell KD lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section **for a period of two years.**